

167
3/2/04

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problems Mailbox.**

THIS PAGE BLANK (USPTO)

#5

367.41233X00



IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant(s): EMMERSON, et al.
Serial No.: Not yet assigned
Filed: March 19, 2002
Title: CLIENT SERVER SYSTEM
Group: Not yet assigned

LETTER CLAIMING RIGHT OF PRIORITY

Honorable Commissioner of
Patents and Trademarks
Washington, D.C. 20231

March 19, 2002


Sir:

Under the provisions of 35 USC 119 and 37 CFR 1.55, the applicant(s) hereby claim(s) the right of priority based on United Kingdom Patent Application No.(s) 0106746.1, filed March 19, 2001.

A certified copy of said United Kingdom Application is attached.

Respectfully submitted,

ANTONELLI, TERRY, STOUT & KRAUS, LLP



Carl I. Brundidge
Registration No. 29,621

CIB/alb
Attachment
(703) 312-6600

THIS PAGE BLANK (USPTO)

THIS PAGE BLANK (USPTO)



INVESTOR IN PEOPLE

The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ



I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.


Signed

Andrew Jones

Dated 12 February 2002

THIS PAGE BLANK (USPTO)

Patents Form 1/77

Patents Act 1977
(Rule 16)The
Patent
Office19MAR01 E614907-1 002716
P01/7700 000-0106746.1**Request for grant of a patent***(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)*

The Patent Office

Cardiff Road
Newport
Gwent NP23 5RH

1. Your reference

PAT 01007 GB

2. Patent application number
(The Patent Office will fill in this part)

0106746.1

19 MAR 2001

3. Full name, address and postcode of the or of each applicant *(underline all surnames)*NOKIA MOBILE PHONES LIMITED
KEILALAHDENTIE 4
02150 ESPOO
FINLANDPatents ADP number *(if you know it)*

If the applicant is a corporate body, give the country/state of its incorporation

FINLAND

5911995006

4. Title of the invention

CLIENT SERVER SYSTEM

5. Name of your agent *(if you have one)*"Address for service" in the United Kingdom to which all correspondence should be sent *(including the postcode)*NOKIA IPR DEPARTMENT
NOKIA HOUSE
SUMMIT AVENUE
FARNBOROUGH
HAMPSHIRE
GU14ONG UKPatents ADP number *(if you know it)*

7577688001

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and *(if you know it)* the or each application number

Country

Priority application number
*(if you know it)*Date of filing
(day / month / year)

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of filing
*(day / month / year)*8. Is a statement of inventorship and of right to grant of a patent required in support of this request? *(Answer 'Yes' if:*

- a) any applicant named in part 3 is not an inventor, or
 - b) there is an inventor who is not named as an applicant, or
 - c) any named applicant is a corporate body.
- See note (ii))

YES

0002142 19-Mar-01 04:45

Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form

Description 11

Claim(s) 3

Abstract 1

Drawing(s) 7

10. If you are also filing any of the following, state how many against each item.

Priority documents

Translations of priority documents

Statement of inventorship and right to grant of a patent (Patents Form 7/77)

Request for preliminary examination and search (Patents Form 9/77)

Request for substantive examination (Patents Form 10/77)

Any other documents (please specify)

11.

I/We request the grant of a patent on the basis of this application.

Signature

Date 19.3.01

KENDRA JONES IAN JOHNSON

12. Name and daytime telephone number of person to contact in the United Kingdom

Dhiren Patel 01252 865285

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention, and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- a) If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.
 b) Write your answers in capital letters using black ink or you may type them.
 c) If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
 d) If you have answered 'Yes' Patents Form 7/77 will need to be filed.
 e) Once you have filled in the form you must remember to sign and date it.
 f) For details of the fee and ways to pay please contact the Patent Office.

1
DUPLICATE

PAT 01007 GB

Client-Server System

5 The present invention relates to a client-server system, and more particularly to a way of downloading content between a client and a server.

10 A client-server system comprises a client terminal and a remote server. In the context of the present invention a client terminal consists in a portable radio communication device such as a mobile phone operating in a communications network. The server is located remotely from the client and is connected with the network. The client terminal and the server in the context of the present invention operate to transfer content and data between one another over the air by means of an air interface.

15 Against this background and in one aspect, the present inventions provides a client-server system as set out in claim 1.

20 By means of the invention, an end user can obtain new secure content for use on his/her terminal from a server quickly, efficiently, and with minimal user input. That is to say, the user is able to download content from a server to his/her terminal without having to carry out a large number of steps on his terminal (such as key depressions) in order to do so.

25 In a specific example, a WAP enabled user terminal (e.g. mobile phone) has stored on a memory thereof an electronic game which the user can play by means of the phone's Games menu software and user interface (e.g. LCD, keys, etc). After a number of plays, the user may wish to have on his/her phone a new (or modified) version of the game (e.g. new level), which new version is available for downloading from a server of the games provider. Accordingly, in a specific arrangement of the present invention, there is provided, as a selectable option embedded in the Games sub-menu, a direct games services link, which the user can select to effect connection to the server. This directly activates, via the phone's WAP browser, a transmission from the mobile phone to the Games server comprising a request for a new games download. This request is received at the server, processed by the server and then if appropriate the requested games download is transmitted by the server via the network to the user's terminal. At the terminal, the new game's

30
35

download is received, processed and stored on the phone's memory as the default version of that particular game. The whole process advantageously is automatic: the user is required only to initiate the request for the new game's download using the direct games services link in the Games sub-menu, and the remaining steps of contacting the games server, downloading, and storing and setting the new games download as default is accomplished without the user having to perform a great many further operations. Hence, in so far as the user is concerned the whole process of obtaining games downloads level is a seamless one.

In this Games download example, the advantages are achieved by the provision primarily of a combination in the mobile phone of a direct games services link in the Games sub-menu and a secure games download authentication means. Because of the direct games services link, the user does not need directly to navigate to and open the mobile phone's WAP browser, and because of the download authentication means, the phone carries out security checks on the games download received from server and if recognised as the coming from a secure source is saved directly in the mobile phone memory as the default version of the game.

The present invention is not limited, in respect of the requesting, downloading and security functionality, to just Games Services, but applies more generally to all forms of multi-media applications services such as music and images.

Other aspects and features of the invention are defined in the appended claims.

In order to aid a better understanding of the present invention, an embodiment of the invention will now be described. This should not be construed as limiting the invention, but merely as an example of a specific way of putting the invention into effect. In particular, the invention will be described with reference to the accompanying drawings in which:

Figure 1 is a schematic of client-server system in accordance with a preferred arrangement of the present invention;

Figure 2 is a block diagram illustrating selected functional aspects of the client server system of Figure 2;

Figure 3 is a flow chart outlining a preferred way of effecting downloading of content

in the client-server system of Figures 1 and 2,

Figure 4 is a hierarchy illustrating a server side download structure;

Figure 5 is a hierarchy illustrating a games data file structure; and
Figure 6 is a game data file structure.

Figure 1 outlines three entities of the present invention, namely a server 21 that
5 holds content for downloading, an end user's mobile phone 31 that is able to
download the content, and an operator network 41 that provides a
telecommunications service to the mobile phone 31. The server 21 has a unique
URL address and using this can be accessed by the end user through the mobile
phone 31 which may be WAP or iMODE enabled.

10 As indicated previously, electronic games software is one example of content for a
mobile phone platform, and in the following example reference will be made to mobile
gaming and games content, although the invention is in no way intended to be limited
to mobile gaming and games content.

15 Mobile gaming is a term used to refer to all aspects of electronic games in the
context of mobile communications. It is not uncommon nowadays for mobile phones
to have, pre-loaded on a memory of the phone, content relating to one or more
electronic games. The games can be played on the mobile phone through the
20 phone's User Interface normally involving the use of the LCD and one or more of the
keys. In order to play a game, the user navigates through the phone's various main
menu options to the Games option and then selects the particular electronic game he
or she wishes to play. Certain keys of the mobile phone's keypad will be pre-
assigned for enabling the user to control certain predetermined features of the game,
25 usually in relation to other features of the game which are under the control of the
software of the game. In this way, the user can be regarded as playing 'against the
computer'. Additionally, in a two (or more) player game, each user (player) has
control over his/her particular game's characters or features with which he/she plays
against the other player(s).

30 In general terms, an electronic game that is designed to be played on a mobile
phone is created by a content provider, who may be the mobile phone manufacturer
or a third party. Typically, the electronic game comprises a games engine that
provides the general functions of the game including instructions and routines for
35 gameplay, for example by drawing of library functions that define how games
characters may interact during game play. The electronic game also has gaming

4

parameters that set out the environmental factors that define the backdrop to the game. Then there are gaming parameters relating to characters of the games, these being entities of the game under user control and with which the user during gameplay associates himself, for instance a team in a sports game, or a fighter in a combat game. In the games content, a combination of these factors define the look and feel of the game, its characters, its objectives, its rules of operation.

In order to afford variation in gameplay, in-built into the games software, typically, is the ability to have different levels of gameplay ranging in complexity. This is usually implemented in the software by making changes to characters, features, aspects and other parameters of the basic gameplay. The content provider additionally creates new levels and/or versions for the game. When new levels and/or versions are applied to the game it modifies the games content. Modified games content has associated with it an identifier tag that identifies the version that has been used in its construction.

The mobile phone manufacturer may embed the games content onto the phone during manufacture, or authorise downloading of the games content onto the phone. Thus the user of the mobile phone is equipped for mobile gaming.

Turning to the end user, the end user is provided with a mobile phone 31 carrying the original games content, and the phone is provided a wireless communication service through the games operator network 41. The end user may begin playing the embedded game in either a stand-alone fashion or interactively with other users. After a number of plays of the game, the user will, in the majority of cases, become increasingly proficient at the game. After continued play, and depending on the skill and ability of the particular user, the end user will most probably master the game. At this stage, ordinarily the challenge of the game would fade and the user would lose interest in the game. However, by means of the preferred arrangement of the invention the user has the option to download from the mobile phone manufacturer's server 21 new levels and/or versions so as to create a new and/or more difficult or different level. The end user accordingly requests using a direct games services link in the Games sub-menu, the download of new levels and/or versions from the server 21 via the operator's network 41. The server 21 holds files of specific type containing the games data. Selecting one of those files results in the download of the file to the mobile phone. After validation by the games engine and game itself by means of a

9-MAR. '01

5

security and authentication process, the game's data file is installed to the phone's permanent memory. A more detailed description of this process follows.

5 Referring to Figure 2, there is shown the end user mobile phone terminal 31, which through the operator network having an operator server 42 can access the mobile phone manufacturer's server 21 having a memory containing downloadable files corresponding to new levels and/or versions (L1, L2, L3) of a particular electronic game. An end user 31 wishing to connect to the server 21 to obtain a games
10 download selects a direct games service link 32 provided as one of the selectable alternatives in the Games sub-menu, for example a selectable menu item called "On-line" (or something similar). The direct games service link is a menu-driven option embedded in the Games sub-menu structure. When the user selects the "On-line" menu item, the software functions to launch the mobile phone's browser 33 (e.g.
15 WAP browser) and load into it a pre-determined URL identification, thus automatically activating a connection to that addressed URL server in order to send a download request to the server. For example a user of Nokia's 3340 phone would select "On-line" from within the Games sub-menu and this would launch the browser to load a file, e.g. www.clubnokia.com/games/3340/index.wml. It may be that the
20 "3340" portion of this example URL, is not included in the file definition, but instead this information is derived by the server from the information which the phone's browser presents to the server.

Alternatively or additionally, the direct games services link option may be configured
25 to appear on the LCD automatically on successful completion of a particular game level. The user could in this case then select to download the next level without having to return to the Games sub-menu.

As indicated above, part of the request may contain a location identifier that, based
30 on pre-programmed characteristics of the mobile phone, serves to place the user at the appropriate part of the server (e.g. automatically at the top of the navigation tree for the user's phone, describe later in relation to Figure 4). Thus, the server is configured to detect the phone type from the information passed to the server by the WAP browser. This allows the server to present the right options/data for that
35 particular phone type. The user can thus access the content in an efficient manner.

The user's request is received first by the network operator at the operator server 42, this is indicated in Figure 3 at block 100. Here a series of checks is carried out in relation to the request in an operator authentication process. As indicated at block 110 in Figure 3, it is checked whether the user subscribes to the appropriate tariff to entitle him/her to access the server in order to obtain the requested service. Accordingly, the user's identity is checked along with his/her tariff subscription. If a positive determination is made, i.e. that the user does subscribe to the appropriate tariff, the operator server forwards the request to the URL address identifying the mobile phone manufacturer's games server 21, as indicated at block 120.

If, on the other hand, the user is identified as not being a subscriber on the appropriate tariff to be allowed the desired service flow passes to block 115 in which the operator server sends a message to the user denying him/her the request. At this juncture, the message may contain information informing the user of steps he may take in order to apply to subscribe to the correct tariff for obtaining games downloads. If at block 115 the user agrees to the appropriate tariff he completes the necessary subscription requirements and flow returns to START.

Returning to the situation where the network operator accepts the user and engages the manufacturer's server to service the request, the user's request received at the server undergoes further authentication and identification at block 130, for instance to check for compatibility between the user's mobile phone and the games download requested. This may be on the basis of an identifier tag associated with the user's terminal software.

On successful authentication at the server, the server provides access to data files that the phone will download via the browser and accordingly may present the user with a series of choices as to which version or level (e.g. L1, L2, or L3) the user would like to download. The server may offer further information on each of the downloadable files. The server is equipped to deal with multiple phone types needing to access similar types of data, or in some cases the same data. The data may or may not be different for each of the phone types (for instance Nokia's 3330 and 3390 mobile phones are variants of the same phone and so in order to support data download for these phones, the content is identical. Conversely, if Nokia's 6210 mobile phone supported data download for the same game as the 3330 mobile phone, the content would be different since the screen resolutions for the two mobile

7

phone models differ. Thus, in order to access the games server there is a common root URL for all the games services, with a means for differentiating content such as a sub-directory for each mobile phone type, as illustrated in Figure 4. Within that structure, the user browses URLs to locate the required downloadable data content. The links when browsing may in some cases take the user to data files that are common with other phones. Within the server memory, games data files are advantageously organised within a common area for downloads by mobile phone model type. This requires sub-division by data version which is used to differentiate such things as screen size differences.

10

Figure 4 gives an example of a user navigation structure for data download for the Nokia game Pairs2 in respect of mobile phone models 3310, 3390 (which have the same data content) and 6210 (which has different content). The illustrated user navigation structure does not necessarily imply that this structure exists as a directory hierarchy on the server, but this is the navigatable structure presented by the WML accessed via the mobile phone browser. In other words, from the header information contained in the request the server can identify the browser for the phone type making the request. This may be by using an initial file which is loaded when accessing the services for that phone type (perhaps 'index.wml'). This file then allows the user to browse the structure shown in Figure 4. The exact composition of the Pairs2 decks and cards that is presented to the server is a matter for server implementation.

15

20

25

The user then makes a selection of the required version. This is indicated at block 140.

30

Alternatively, the server may detect what version/level is currently stored on the user's handset by virtue of a games level identifier tag that accompanies the user's games download request, and on that basis only allow the user to download the next successive version/level.

35

The selected games download then undergoes further processing in the server. Initially, the selection passes to a controller 22 in Figure 2 that checks at block 145 in Figure 3 that the requested game is the appropriate one for the particular user to play. For instance, if the user is a novice at a particular game the server ensures that the game to be sent to the user is the level 1 (i.e. easiest) version of the game.

Such a check may be made by reference to a user profile that may be stored on the server (for example based on some pre-existing registration), or uploaded to the server from the phone. The games controller 22 then accesses the memory storage 23 holding the appropriate games download data file using a memory address, and from there retrieves a copy of the games download file, as indicated at block 150 in Figure 3. Following appropriate checks, the games download file is dispatched from the server and transmitted according to block 160 via the operator server 42 to the mobile phone. In downloading the games data file, the transport protocol presents certain pre-determined codes or qualifiers with the data file which serve to provide an indication of the server's identity, this is indicated at block 170. Specifically, the HTTP header may indicate, through use of a specific mime type in a form such as: "Content-Type: application/X-NokiaGameData", the type of data that is being downloaded. This provides information on what processes can be applied to the file. When received, this indicates to the mobile phone that the games engine should receive this content. Furthermore, the originating URL of the game data may be used as a means of validating the authenticity of the data. The mime type is used advantageously for any number of games which the mobile phone's game engine may support, by removing the need to define a new mime type for each game.

On receipt of the games download file at the mobile phone, a message is displayed on the phone's LCD indicating that the games download has been delivered. The mobile phone's processor carries out a series of error checks to ensure that all the data has been faithfully received (block 190 in Figure 3), if not a void games data file is registered at block 200. In addition to the error checks, the mobile phone's processor invokes a security and authentication process, as given by block 210. In this process, the phone checks that the correct games download file has been received and from the correct server.

To carry out the security and authentication process, the mobile phone's browser is configured to examine the information passed between the server and the phone and more particularly to recognise and accept a file type for games download data (e.g. for Nokia games download data). Specifically, the games download data file is recognised by the browser by the mime type (e.g. application/x-Nokia-GameData) and can be passed first to the game engine and then by the game engine to the specific game for security and authentication checks.

9

The browser calls a handler from the games engine to process the games download data file. The handler is based on the transport mechanism employed in the mobile phone (e.g. WAP, SMS or iMODE) and serves to signal the arrival of data.

- 5 By calling on the handler, part of the authentication is performed by the games engine, and another part is performed by the game itself since only the game itself can recognise certain play features of the game.

- 10 If the browser sends the game application the source URL in the message with the data a check is made that the source is valid e.g. www.clubnokia.com/games/, and the content may be rejected if it is determined from the check that it has not been sent from a valid source. Accordingly, if the games download file is verified as being from an authentic source, it is accepted, if not the games download is rejected as void data.

- 15 If void game data is registered a notification is sent to the server via the operator of the rejected game (block 220). If the games download data file is accepted, it is stored to the mobile phone's memory, as shown at block 230 in Figure 3.

- 20 The downloaded game data file structure is described with reference to Figure 6:
Game engine data header: Data used by the game engine to validate the file and route the data to the correct game; Common game data header: data used by all games to validate the file and identify it; Game specific data: the data actually used when running the game to revise the gameplay.

- 25 Storage onto the phone's memory, may be carried out by the user through use of the menu options to save the game onto the phone memory. Alternatively, there may be automatic saving to memory on verification of error free receipt of a secure game. The data file would be stored in a part of memory that does not depend upon the
30 phone remaining powered up, or with a charged battery.

- Storing the games download into the mobile phone memory modifies the previously stored games data for instance by overwriting library data or aspects of in-game data to provide modified content thereby avoiding taking up substantially extra memory
35 space.

10

The step of saving the games download on the phone causes a signal to be transmitted to the server via the operator that the games download has been accepted and saved in the mobile phone memory. This acts as a confirmation of receipt and acceptance by the user as shown at block 200.

5

Transfer of signals between the user's mobile phone and the server may use any appropriate modes such as WAP and SMS, advantage being taken of security protocols established under these modes. For example, in order to establish a secure session between the server and the mobile phone there may be an exchange of public keys, followed an exchange of secret keys.

10

Thus it should be noted that this specific embodiment of the invention, determines whether or not the received games download is from a 'trusted' server, and this accordingly blocks downloading of games content from unauthorised sources. A trusted server is one that the mobile phone recognises is a server authorised to provide content for download to the mobile phone, and this may be on the basis of information pre-loaded, flashed or even downloaded to the phone's memory, and may be implemented for example in the form of a look-up table. Advantageously, the invention provides a safeguard against the content crashing the phone.

20

Various arrangements are envisaged for schemes for payment by the user for the downloaded content. One arrangement is to set a limit in the server of number of times a single user could download a purchased piece of data. This would require database entries in the server to track which users had downloaded which data and monitor how many times the content has been downloaded. The same data could be downloaded again by paying again. This allows for reloading of data. Another arrangement is to have the games engine keep track of data it had ever downloaded. Whenever data was detected which was not previously registered on that mobile phone, the phone would prompt the user to send a message (e.g. SMS) to the server with a pre-defined message. This message may contain the data identification and a reverse billing process is set up on the received messages to the server. Then instead of paying initially for the data content, the user gets billed for the act of "unlocking" it on the device.

30

It should be understood that the specific description given above provides merely on way of embodying the present invention, and that the present invention may be used

35

in other forms and for other types of content download with it departing from its essential attributes.

5 Thus, reference should thus be made to the appended claims and other general statements herein rather than to the foregoing description as indicating the scope of the invention.

10 Furthermore, each feature disclosed in this specification (which terms includes the claims) and/or shown in the drawings may be incorporated in the invention independently of other disclosed and/or illustrated features. In this regard, the invention includes any novel feature or combination of features disclosed herein either explicitly or any generalisation thereof irrespective of whether or not it relates to the claimed invention or mitigates any or all of the problems addressed.

15 The appended abstract as file herewith is included in the specification by reference.

12

Claims**1. A client-server system comprising****a client terminal and a remote server,**

5 wherein the client terminal comprises a portable radio communication device
 having a user interface and authentication means,

 the user interface comprising

 a plurality of user selectable menu applications and a browser
 application,

10 and operable to request content stored at the server,

 wherein one or more of the menu applications includes,
 embedded in a sub-menu thereof, a user selectable direct
 download link comprising the server address, whereby in
 response to user selection of the direct download link from
15 the sub-menu the browser application controls the radio
 communication device to transmit a signal to connect to the
 server,

 and the authentication means comprising means for checking validation
 data of content downloaded from the server,

20 and wherein the remote server comprises

 means for downloading said content to the portable radio
 communication device whereby validation data is associated with said
 content so as to be identifiable by said authentication means as
 originating from the said server.

25

2. A client terminal comprising a portable radio communication device having a user
interface and authentication means, the user interface comprising a plurality of user
selectable menu applications and a browser application operable to request content
stored at the server, wherein one or more of the menu applications includes,
30 embedded in a sub-menu thereof, a user selectable direct download link comprising
 the server address, whereby in response to user selection of the direct download link
 from the sub-menu the browser application controls the radio communication device
 to transmit a signal to connect to the server, and the authentication means
 comprising means for security checking validation data associated with the content
35 downloaded from the server.

13

3. A system or terminal as defined in any preceding claim, wherein the terminal comprises means automatically, after said checking of the validation data, for storing the downloaded content to a memory of the terminal as a default memory setting.
- 5 4. A system or terminal as defined in any preceding claim, wherein said validation data comprises download transport protocol HTTP header and the authentication means examines said header.
- 10 5. A computer program product on a portable radio communication device, the product comprising a user interface comprising a plurality of user selectable menu applications and a browser application, wherein one or more of the menu applications includes, embedded in a sub-menu thereof, a user selectable direct download link comprising a server address, whereby in response to user selection of the direct download link from the sub-menu the browser application controls the radio
- 15 communication device to transmit a signal to connect to the server.
6. A computer program product on a portable radio communication device, the product comprising authentication means for security checking content downloaded from a server to the device so as to determine whether or not the download d
- 20 content is from a trusted server.
7. A method for downloading content to a client terminal consisting of a portable radio communication device from a server, the portable radio communication device having a user interface comprising a plurality of user selectable menu applications
- 25 and a browser application, wherein one or more of the menu applications includes, embedded in a sub-menu thereof, a user selectable direct download link comprising the server address, whereby in response to user selection of the direct download link from the sub-menu the browser application controls the radio
- 30 communication device to transmit a signal to connect to the server, the method comprising selecting said direct download link from the sub-menu so as to request content stored at the server, processing and downloading said content from the server to the portable radio communication device, and
- 35 security checking the content downloaded from the server.

14

8. A client terminal comprising a portable radio communication device having a user interface comprising a plurality of user selectable menu applications and a browser application, wherein one or more of the menu applications includes, embedded in a sub-menu thereof, a user selectable direct download link comprising a server address, whereby in response to user selection of the direct download link from the sub-menu the browser application controls the radio communication device to transmit a signal to connect to the server.
9. A client terminal comprising a portable radio communication device having a user interface comprising a plurality of user selectable menu applications and a browser application, means for requesting content stored at a server, authentication means for security checking the content downloaded from the server so as to determine whether or not the downloaded content is from a trusted server.
10. A client-server system or client terminal substantially as hereinbefore described with reference to or as shown in the accompanying Figures.


15

Abstract


This invention relates to a way of downloading content from a server to a mobile phone in which the server can be accessed directly from within a phone menu application. The content is thus downloaded from the server to the mobile phone, and accompanying the content is HTTP header that indicates the source URL of the server. The content once received at the phone from the server is then subjected to examination whereby the mobile phones determines whether or not the downloaded content is from a trusted server.

THIS PAGE BLANK (USPTO)

1/7



21



41

31




FIGURE 1

THIS PAGE BLANK (USPTO)




FIGURE 2

THIS PAGE BLANK (USPTO)

3/7





FIGURE 3

THIS PAGE BLANK (USPTO)



THIS PAGE BLANK (USPTC)

5/7




FIGURE 4

THIS PAGE BLANK (USPTO)

6/7




FIGURE 5

THIS PAGE BLANK (USPTO)

7/7




FIGURE 6

THIS PAGE BLANK (USPTO)

THIS PAGE BLANK (USPTO)